

Constant Contact Authenticate a Connector Instance

Last Modified on 03/16/2020 5:58 am EDT

On this page

You can authenticate with Constant Contact to create your own instance of the Constant Contact connector through the UI or through APIs. Once authenticated, you can use the connector instance to access the different functionality offered by the Constant Contact platform.

Authenticate Through the UI

Use the UI to authenticate with Constant Contact and create a connector instance. Because you authenticate with Constant Contact via OAuth 2.0, all you need to do is add a name for the instance. After you create the instance, you'll log in to Constant Contact to authorize SAP Cloud Platform Open Connectors access to your account. For more information about authenticating a connector instance, see [Authenticate a Connector Instance \(UI\)](#).

After successfully authenticating, we give you several options for next steps. [Make requests using the API docs](#) associated with the instance, [map the instance to a common resource](#), or [use it in a formula template](#).

Authenticate Through API

Authenticating through API is a multi-step process that involves:

- [Getting a redirect URL](#). This URL sends users to the vendor to log in to their account.
- [Authenticating users and receiving the authorization grant code](#). After the user logs in, the vendor makes a callback to the specified url with an authorization grant code.
- [Authenticating the connector instance](#). Using the authorization code from the vendor, authenticate with the vendor to create a connector instance at SAP Cloud Platform Open Connectors.

Getting a Redirect URL

Use the following API call to request a redirect URL where the user can authenticate with the API provider. Replace `{keyOrId}` with the connector key, `constantcontact`.

```
curl -X GET /elements/{keyOrId}/oauth/url?apiKey=&apiSecret=&callbackUrl=&siteAddress=
```

Note: If you want to provide your application users with the ability to sign up with Constant Contact, include `newUser=True` in the query parameters as shown below.

```
curl -X GET /elements/{keyOrId}/oauth/url?newUser=True&apiKey=&apiSecret=&callbackUrl=&siteAddress=
```

Query Parameters

| Query Parameter | Description |
|-----------------|--|
| apiKey | The key obtained from registering your app with the provider. This is the Client ID that you recorded in API Provider Setup section. |
| apiSecret | The secret obtained from registering your app with the provider. This is the Client Secret that you recorded in API Provider Setup section. |
| callbackUrl | The URL that will receive the code from the vendor to be used to create a connector instance. |
| newUser | <i>Optional.</i> Include <code>newUser=true</code> to redirect a user to the account signup page instead of the login page. |

Example cURL

```
curl -X GET \
  'https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/elements/constantcontact/oauth/url?apiKey=fake_api_key&apiSecret=fake_api_secret&callbackUrl=https://www.mycoolapp.com/auth&state=constantcontact' \
```

Example Response

Use the `oauthUrl` in the response to allow users to authenticate with the vendor.

```
{
  "oauthUrl": "https://oauth2.constantcontact.com/oauth2/oauth/siteowner/
authorize?response_type=code&client_id=6rja8budeg8gkpq9fhu3g4ha&redirect_ur
i=https%3A%2F%2Fhttpbin.org%2Fget",
  "element": "constantcontact"
}
```

Authenticating Users and Receiving the Authorization Grant Code

Provide the response from the previous step to the users. After they authenticate, Constant Contact provides the following information in the response:

- code
- username

| Response Parameter | Description |
|--------------------|--|
| code | The Authorization Grant Code required by SAP Cloud Platform Open Connectors to retrieve the OAuth access and refresh tokens from the endpoint. |
| username | The Constant Contact user name of the authenticated user. |

Note: If the user denies authentication and/or authorization, there will be a query string parameter called `error` instead of the `code` parameter. In this case, your application can handle the error gracefully.

Authenticating the Instance

Use the `/instances` endpoint to authenticate with Constant Contact and create a connector instance. If you are configuring events, see the [Events section](#).

Note: The endpoint returns a connector instance token and id upon successful completion. Retain the token and id for all subsequent requests involving this connector instance.

To create a connector instance:

1. Construct a JSON body as shown below (see [Parameters](#)):

```
{
  "element": {
    "key": "constantcontact"
  },
  "providerData": {
    "code": ""
  },
  "configuration": {
    "oauth.callback.url": "",
    "oauth.api.key": "",
    "oauth.api.secret": "",
    "filter.response.nulls": true
  },
  "tags": [
    ""
  ],
  "name": ""
}
```

2. Call the following, including the JSON body you constructed in the previous step:

```
POST /instances
```

Note: Make sure that you include the User and Organization keys in the header. For more information, see [Authorization Headers, Organization Secret, and User Secret](#).

3. Locate the `token` and `id` in the response and save them for all future requests using the connector instance.

Example cURL

```

curl -X POST \
  https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/instances \
  -H 'authorization: User , Organization ' \
  -H 'content-type: application/json' \
  -d '{
  "element": {
    "key": "constantcontact"
  },
  "providerData": {
    "code": "xoz8AFqScK2ngM04kSSM"
  },
  "configuration": {
    "oauth.callback.url": "",
    "oauth.api.key": "",
    "oauth.api.secret": ""
  },
  "tags": [
    "Docs"
  ],
  "name": "API Instance"
}'

```

Parameters

API parameters not shown in the SAP Cloud Platform Open Connectors are in

`code formatting`.

Note: Event related parameters are described in [Events](#).

| Parameter | Description | Data Type |
|---------------------------------|---|-----------|
| 'key' | The connector key. constantcontact | string |
| Name <code>name</code> | The name for the connector instance created during authentication. | Body |
| <code>oauth.callback.url</code> | The URL where you want to redirect users after they grant access. This is the Callback URL that you noted in the API Provider Setup section. | |
| <code>oauth.api.key</code> | The Client ID from Constant Contact. This is the Client ID that you noted in the API Provider Setup section. | string |
| | | |

| | | |
|--|--|------------------------|
| <code>oauth.api.secret</code> Parameter | The Client Secret from Constant Contact. This is the Client Secret that you noted in the API Provider Setup section. | String Data Type |
| tags | <i>Optional.</i> User-defined tags to further identify the instance. | string |

Example Response for an Authenticated Connector Instance

```
{
  "id": 12345,
  "name": "API for Docs",
  "token": "3sU/S/kZD36BaABPS7EAuSGHF+lwsthT+mvoukiE",
  "element": {
    "id": ,
    "name": "Constant Contact",
    "hookName": "ConstantContactHook",
    "key": "constantcontact",
    "description": "Add a Constant Contact instance to connect your exist
ing or new Constant Contact account to the Marketing Hub, allowing you to m
anage campaigns, lists, contacts etc. across multiple Marketing Connectors.
You will need your Constant Contact account information to add an instance.
",
    "image": "elements/provider_constantcontact.png",
    "active": true,
    "deleted": false,
    "typeOauth": false,
    "trialAccount": false,
    "resources": [ ],
    "transformationsEnabled": true,
    "bulkDownloadEnabled": true,
    "bulkUploadEnabled": true,
    "cloneable": true,
    "extendable": false,
    "beta": true,
    "authentication": {
      "type": "oauth2"
    },
    "extended": false,
    "hub": "marketing",
    "protocolType": "http",
    "parameters": [ ],
    "elementId": 3929,
    "provisionInteractions": [],
    "valid": true,
    "disabled": false,
    "maxCacheSize": 0,
    "cacheTimeToLive": 0,
    "configuration": {
      }
    }
  }
}
```

```
"eventsEnabled": false,  
"traceLoggingEnabled": false,  
"cachingEnabled": false,  
"externalAuthentication": "none",  
"user": {  
  "id": 12345  
}  
}  
}
```
