

# MailChimp v3.0 Events

Last Modified on 12/30/2019 8:32 pm EST

SAP Cloud Platform Open Connectors supports events via polling or webhooks depending on the API provider. For more information about our Events framework, see [Events Overview](#).

## Supported Events and Resources

SAP Cloud Platform Open Connectors supports webhook events for MailChimp. After receiving an event, SAP Cloud Platform Open Connectors standardizes the payload and sends an event to the configured callback URL of your authenticated connector instance. For more information about webhooks at MailChimp including the currently available webhooks, see [their webhooks documentation](#).

## Configure Webhooks Through the UI

To configure webhooks through the UI, follow the same steps to authenticate a connector instance, and then turn on events. For more information, see [Authenticate an Connector Instance with Events \(UI\)](#) or the connector-specific authentication topic.

## Configure Webhooks Through API

Use the `/instances` endpoint to authenticate with MailChimp and create a connector instance with webhooks enabled.

**Note:** The endpoint returns a connector instance token and id upon successful completion. Retain the token and id for all subsequent requests involving this connector instance.

To authenticate a connector instance with webhooks:

1. Get an authorization grant code by completing the steps in [Getting a redirect URL and Authenticating users and receiving the authorization grant code](#).
2. Construct a JSON body as shown below (see [Parameters](#)):

```
{
  "element": {
    "key": "mailchimpv3"
  },
  "providerData": {
    "code": ""
  },
  "configuration": {
    "oauth.api.key": "",
    "oauth.api.secret": "",
    "oauth.callback.url": "",
    "event.notification.enabled": true,
    "event.notification.callback.url": ""
  },
  "tags": [
    ""
  ],
  "name": ""
}
```

3. Call the following, including the JSON body you constructed in the previous step:

```
POST /instances
```

**Note:** Make sure that you include the User and Organization keys in the header. For more information, see [Authorization Headers, Organization Secret, and User Secret](#).

4. Locate the `token` and `id` in the response and save them for all future requests using the connector instance.

## Example cURL

```
curl -X POST \
  https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/instances \
  -H 'authorization: User , Organization ' \
  -H 'content-type: application/json' \
  -d '{
    "element": {
      "key": "mailchimpv3"
    },
    "providerData": {
      "code": "xoz8AFqScK2ngM04kSSM"
    },
    "configuration": {
      "oauth.api.key": "Rand0MAP1-key",
      "oauth.api.secret": "fak3AP1-s3Cr3t",
      "oauth.callback.url": "https://mycoolapp.com",
      "event.notification.enabled": true,
      "event.notification.callback.url": "https://mycoolapp.com/events"
    },
    "tags": [
      "Docs"
    ],
    "name": "API Instance"
  }'
```

## Parameters

API parameters not shown in the SAP Cloud Platform Open Connectors are in

`code formatting`.

Parameter	Description	Data Type
<code>key</code>	The connector key. mailchimpv3	string
<code>code</code>	The authorization grant code returned from the API provider in an OAuth 2.0 authentication workflow. SAP Cloud Platform Open Connectors uses the code to retrieve the OAuth access and refresh tokens from the endpoint.	string
Name	The name of the connector instance	

name	created during authentication.	Body Data
Parameter	<b>Description</b> The API key or client ID obtained from	<b>Type</b>
oauth.api.key	registering your app with the provider. This is the <b>Key Name</b> that you recorded in the <a href="#">API Provider Setup section</a> .	string
oauth.api.secret	The client secret obtained from registering your app with the API provider. This is the <b>Secret Name</b> that you recorded in the <a href="#">API Provider Setup section</a> .	string
oauth.callback.url	The URL that the API provider returns a user to after they authorize access. This is the <b>Callback URL Name</b> that you recorded in the <a href="#">API Provider Setup section</a> .	string
Events Enabled event.notification.enabled	<i>Optional.</i> Identifies that events are enabled for the connector instance. Default: <code>false</code> .	boolean
Event Notification Callback URL event.notification.callback.url	The URL where you want SAP Cloud Platform Open Connectors to send the events.	string
Callback Notification Signature Key event.notification.signature.key	<i>Optional.</i> A user-defined key for added security to show that events have not been tampered with.	string
tags	<i>Optional.</i> User-defined tags to further identify the instance.	string