

Shopify Events

Last Modified on 01/30/2019 5:48 pm EST

On this page

SAP Cloud Platform Open Connectors supports events via polling or webhooks depending on the API provider. For more information about our Events framework, see [Events Overview](#).

Supported Events and Resources

SAP Cloud Platform Open Connectors supports webhook events for Shopify. After receiving an event, SAP Cloud Platform Open Connectors standardizes the payload and sends an event to the configured callback URL of your authenticated connector instance. For more information about webhooks at Shopify including the currently available webhooks, see [their webhooks documentation](#).

Configure Webhooks Through the UI

To configure webhooks through the UI, follow the same steps to authenticate a connector instance, and then turn on events. For more information, see [Authenticate an Connector Instance with Events \(UI\)](#) or the connector-specific authentication topic.

Configure Webhooks Through API

Use the `/instances` endpoint to authenticate with Shopify and create a connector instance with webhooks enabled.

Note: The endpoint returns a connector instance token and id upon successful completion. Retain the token and id for all subsequent requests involving this connector instance.

To authenticate a connector instance with webhooks:

1. Get an authorization grant code by completing the steps in [Getting a redirect URL and Authenticating users and receiving the authorization grant code](#).
2. Construct a JSON body as shown below (see [Parameters](#)):

```
{
  "element": {
    "key": ""
  },
  "providerData": {
    "code": ""
  },
  "configuration": {
    "oauth.callback.url": "",
    "oauth.api.key": "",
    "oauth.api.secret": "",
    "event.notification.enabled": true,
    "shopify.webhook.topics": "",
    "event.notification.callback.url": "",
    "event.notification.signature.key": ""
  },
  "tags": [
    ""
  ],
  "name": ""
}
```

3. Call the following, including the JSON body you constructed in the previous step:

```
POST /instances
```

Note: Make sure that you include the User and Organization keys in the header. For more information, see [Authorization Headers](#), [Organization Secret](#), and [User Secret](#).

4. Locate the `token` and `id` in the response and save them for all future requests using the connector instance.

Example cURL

```
curl -X POST \
  https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/instances \
  -H 'authorization: User , Organization ' \
  -H 'content-type: application/json' \
  -d '{
    "element": {
      "key": ""
    },
    "providerData": {
      "code": "xoz8AFqScK2ngM04kSSM"
    },
    "configuration": {
      "oauth.callback.url": "https://mycoolapp.com",
      "oauth.api.key": "xxxxxxxxxxxxxxxxxxxx",
      "oauth.api.secret": "xxxxxxxxxxxxxxxxxxxx",
      "event.notification.enabled": true,
      "shopify.webhook.topics": "orders/create, orders/updated, customers/create",
      "event.notification.callback.url": "https://mycoolapp.com/events",
      "event.notification.signature.key": "xxxxxxxxxxxxxxxxxxxx"
    },
    "tags": [
      "Docs"
    ],
    "name": "API Instance"
  }'
```

Parameters

API parameters not shown in the SAP Cloud Platform Open Connectors are in

`code formatting`.

Parameter	Description	Data Type
<code>key</code>	The connector key.	string
<code>code</code>	The authorization grant code returned from the API provider in an OAuth2 authentication workflow.	string
Name <code>name</code>	The name for the connector instance created during authentication.	Body
	The URL where you want to redirect users after they grant access. This is	

Parameter	Description	Data Type
<code>oauth.callback.url</code>	the Callback URL that you noted in the API Provider Setup section.	
<code>oauth.api.key</code>	The Client ID from Shopify. This is the Client ID that you noted in the API Provider Setup section.	string
<code>oauth.api.secret</code>	The Client Secret from Shopify. This is the Client Secret that you noted in the API Provider Setup section.	string
Events Enabled <code>event.notification.enabled</code>	<i>Optional.</i> Identifies that events are enabled for the connector instance. Default: <code>false</code> .	boolean
Event Notification Callback URL <code>event.notification.callback.url</code>	The URL where you want SAP Cloud Platform Open Connectors to send the events.	string
Callback Notification Signature Key <code>event.notification.signature.key</code>	<i>Optional.</i> A user-defined key for added security to show that events have not been tampered with.	string
Webhook Topics <code>shopify.webhook.topics</code>	Comma separated list of supported webhook topics that you want to monitor. See Shopify's webhooks documentation for a list of supported webhooks.	string
tags	<i>Optional.</i> User-defined tags to further identify the instance.	string