

# PostgreSQL Authenticate a Connector

Last Modified on 12/30/2019 9:22 pm EST

## Create Instance Directly via IP Address and Port Number

The following is required to create a PostgreSQL connector Instance:

- Database Host: e.g. `123.123.1.123:3306`
- Database Name
- Database Username
- Database Password
- Database Schema Name (**OPTIONAL**: Schema name from where the database schema needs to be read from, if nothing mentioned connects to `public` schema)
- Database Tables (**OPTIONAL**: Can connect a set of tables i.e. contacts, accounts or prefixed tables, i.e. `data_*` via comma separated list)

## Step 1. Create an Instance

To provision your PostgreSQL connector, use the /instances API.

Below is an example of the provisioning API call.

- **HTTP Headers:** Authorization- User , Organization
- **HTTP Verb:** POST
- **Request URL:** /instances
- **Request Body:** Required – see below
- **Query Parameters:** none

Description: token is returned upon successful execution of this API. This token needs to be retained by the application for all subsequent requests involving this connector instance.

A sample request illustrating the /instances API is shown below.

HTTP Headers:

```
Authorization: User , Organization
```

This instance.json file must be included with your instance request. Please fill your information to provision. The “key” into PostgreSQL is "postgresql". This will need to be entered in the “key” field below depending on which connector you wish to instantiate.

## Instance Configuration

The content in the `configuration` section or nested object in the body posted to the `POST /instances` or `PUT /instances/{id}` APIs varies depending on which connector is being instantiated. However, some configuration properties are common to all connectors and available to be configured for all connectors. These properties are -

- `event.notification.enabled` : This property is a `boolean` property, and determines if event reception (via `webhook` or `polling` ) is enabled for the connector instance. This property defaults to *false*.
- `event.vendor.type` : When `event.notification.enabled` property is set to *true*, this property determines the mechanism to use to receive or fetch changed events from the service endpoint. The supported values are `webhook` and `polling` . Most connectors support one mechanism or the other, but some like Salesforce.com support both mechanisms. This property is *optional*.
- `event.notification.type` : This property can be used to determine how an event notification should be sent to the consumer of the connector instance, in most cases your application. Currently, `webhook` is the only supported value for this property. This means that when an event is received by the connector instance, it will get forwarded to the provided `event.notification.callback.url` via a `webhook` to you. This property is *optional*.
- `event.notification.callback.url` : As mentioned above, the value of this property is an `http` or `https` URL to which we will post the event for consumption by your application. This property is *optional*.
- `filter.response.nulls` : This property defaults to *true*, i.e., it's `boolean` property, and determines if `null` values in the response `JSON` should or should not be filtered from the response returned to the consuming application. By default, all `null` values are filtered from the response before sending the response to the consuming application.