

Infusionsoft Marketing Automation Authenticate a Connector

Last Modified on 03/16/2020 9:26 pm EDT

You can authenticate with Infusionsoft to create your own instance of the Infusionsoft Marketing Automation connector through the UI or through APIs. Once authenticated, you can use the connector instance to access the different functionality offered by the Infusionsoft platform.

Authenticate Through the UI

Use the UI to authenticate with Infusionsoft and create a connector instance. Because you authenticate with Infusionsoft via OAuth 2.0, all you need to do is add a name for the instance and provide your Infusionsoft server name and encrypted key. After you create the instance, you'll log in to Infusionsoft to authorize SAP Cloud Platform Open Connectors access to your account. For more information about authenticating a connector instance, see [Authenticate a Connector Instance \(UI\)](#).

After successfully authenticating, we give you several options for next steps. [Make requests using the API docs](#) associated with the instance, [map the instance to a common resource](#), or [use it in a formula template](#).

Authenticate Through API

Authenticating through API is similar to authenticating via the UI. Instead of clicking and typing through a series of buttons, text boxes, and menus, you will instead send a request to our `/instances` endpoint. The end result is the same, though: an authenticated connector instance with a **token** and **id**.

Authenticating through API follows a multi-step OAuth 2.0 process that involves:

1

Redirect URL



2

Authenticate Users



3

Authenticate Instance

- [Getting a redirect URL](#). This URL sends users to the vendor to log in to their account.
- [Authenticating users and receiving the authorization grant code](#). After the user logs in, the vendor makes a callback to the specified url with an authorization grant code.
- [Authenticating the connector instance](#). Using the authorization code from the vendor, authenticate with the vendor to create a connector instance at SAP Cloud Platform Open Connectors.

Getting a Redirect URL

1

Redirect URL



2

Authenticate Users



3

Authenticate Instance

Use the following API call to request a redirect URL where the user can authenticate with the service provider. Replace `{keyOrId}` with the connector key, `infusionsoftmarketing`.

```
curl -X GET /elements/{keyOrId}/oauth/url?apiKey=&apiSecret=&callbackUrl=&siteAddress=
```

Query Parameters

Query Parameter	Description
apiKey	The API key or client ID obtained from registering your app with the provider. This is the client_id that you recorded in the API Provider Setup section.
apiSecret	The client secret obtained from registering your app with the API provider. This is the client_secret that you recorded in the API Provider Setup section.
callbackUrl	The URL that the API provider returns a user to after they authorize access. This is the Callback URL that you recorded in the API Provider Setup section.

Example cURL

```
curl -X GET \  
  'https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/elements/infusionsoftmarketing/oauth/url?apiKey=fake_api_key&apiSecret=fake_api_secret&callbackUrl=https://www.mycoolapp.com/auth&state=infusionsoftmarketing' \  
  \
```

Example Response

Use the `oauthUrl` in the response to allow users to authenticate with the vendor.

```
{
  "oauthUrl": "https://signin.infusionsoft.com/app/oauth/authorize?scope=full&response_type=code&redirect_uri=https%3A%2F%2Fhttpbin.org%2Fget&state=infusionsoftcrm&client_id=4ynetc9z7v6vajwkvxvgxj",
  "element": "infusionsoftcrm"
}
```

Authenticating Users and Receiving the Authorization Grant Code

1
Redirect URL



2
Authenticate Users



3
Authenticate Instance

Provide the response from the previous step to the users. After they authenticate, Infusionsoft Marketing Automation provides the following information in the response:


- code
- state

Response Parameter	Description

Response code Parameter	Description: The authorization grant code returned from the API provider in an OAuth 2.0 authentication workflow. SAP Cloud Platform Open Connectors uses the code to retrieve the OAuth access and refresh tokens from the endpoint.
state	A customizable identifier, typically the connector key (<code>infusionsoftmarketing</code>)

Note: If the user denies authentication and/or authorization, there will be a query string parameter called `error` instead of the `code` parameter. In this case, your application can handle the error gracefully.

Authenticating the Connector Instance



Use the `/instances` endpoint to authenticate with Infusionsoft Marketing Automation and create a connector instance.

Note: The endpoint returns a connector instance token and id upon successful completion. Retain the token and id for all subsequent requests involving this connector instance.

To authenticate a connector instance:

1. Construct a JSON body as shown below (see [Parameters](#)):

```
{
  "element": {
    "key": "infusionsoftmarketing"
  },
  "providerData": {
    "code": ""
  },
  "configuration": {
    "oauth.callback.url": "",
    "oauth.api.key": "",
    "oauth.api.secret": "",
    "infusionsoft.server": "",
    "infusionsoft.private.key": ""
  },
  "tags": [
    ""
  ],
  "name": ""
}
```

2. Call the following, including the JSON body you constructed in the previous step:

```
POST /instances
```

Note: Make sure that you include the User and Organization keys in the header. For more information, see [Authorization Headers, Organization Secret, and User Secret](#).

3. Locate the `token` and `id` in the response and save them for all future requests using the connector instance.

Example cURL

```

curl -X POST \
  https://api.openconnectors.us2.ext.hana.ondemand.com/elements/api-v2/instances \
  -H 'authorization: User , Organization ' \
  -H 'content-type: application/json' \
  -d '{
  "element": {
    "key": "infusionsoftmarketing"
  },
  "providerData": {
    "code": "xxxxxxxxxxxxxxxxxxxxxxxxxxxx"
  },
  "configuration": {
    "oauth.callback.url": "https://mycoolapp.com",
    "oauth.api.key": "xxxxxxxxxxxxxxxxxxxx",
    "oauth.api.secret": "xxxxxxxxxxxxxxxxxxxxxxxxxxxx",
    "infusionsoft.server": "dt123.infusionsoft.com",
    "infusionsoft.private.key": "47dxxxxxxxxxxxxxxxxxxxx"
  },
  "tags": [
    "Docs"
  ],
  "name": "API Instance"
}'

```

Parameters

API parameters not shown in SAP Cloud Platform Open Connectors are in

`code formatting`.

Parameter	Description	Data Type
<code>key</code>	The connector key. infusionsoftmarketing	string
<code>code</code>	The authorization grant code returned from the API provider in an OAuth 2.0 authentication workflow. SAP Cloud Platform Open Connectors uses the code to retrieve the OAuth access and refresh tokens from the endpoint.	string
Name <code>name</code>	The name of the connector instance created during authentication.	string
	The API key or client ID obtained from registering	

Parameter	Description	string Data Type
<code>oauth.api.key</code>	your app with the provider. This is the client_id that you noted in the API Provider Setup section.	string
<code>oauth.api.secret</code>	The client secret obtained from registering your app with the API provider. This is the client_secret that you noted in the API Provider Setup section.	string
<code>oauth.callback.url</code>	The API key or client ID obtained from registering your app with the provider. This is the Callback URL that you noted in the API Provider Setup section.	string
Infusionsoft Server <code>infusionsoft.server</code>	The account portion of your Infusionsoft URL. For example, if your account url is <code>https://dt123.infusionsoft.com</code> enter <code>dt364.infusionsoft.com</code> . You can also enter <code>https://dt123.infusionsoft.com</code> .	string
Infusionsoft Encrypted Key <code>infusionsoft.private.key</code>	The encrypted API key that you noted in the API Provider Setup section.	string
tags	<i>Optional.</i> User-defined tags to further identify the instance.	string

Example Response for an Authenticated Connector Instance

```
{
  "id": 1234,
  "name": "Test",
  "token": "a5y4EtYt+ZYRpnIBD7gkQtthDebK8qKVU=",
  "element": {
    "id": 126,
    "name": "Infusionsoft Beta",
    "key": "infusionsoftmarketing",
    "description": "Add an Infusionsoft Instance to connect your existing Infusionsoft account to the Marketing Hub, allowing you to manage contacts, leads, accounts, opportunities etc. across multiple Marketing Connectors. You will need your Infusionsoft account information to add an instance.",
    "image": "http://www.sagepay.co.uk/files/styles/img_220x220/public/partner-logo/infusionsoft-220px.png?itok=yDDuLcdL",
    "active": true,
    "deleted": false,
    "typeOauth": false,
    "trialAccount": false,
    "resources": [],
    "transformationsEnabled": true,
    "authentication": {
      "type": "oauth2"
    }
  }
}
```



```
    type : oauth2
  },
  "hub": "marketing",
  "parameters": []
},
"provisionInteractions": [],
"valid": true,
"disabled": false,
"maxCacheSize": 0,
"cacheTimeToLive": 0,
"configuration": {
  "oauth.api.secret": "INFUSIONSOFT_API_SECRET",
  "base.url": "https://fm260.infusionsoft.com/api/xmlrpc",
  "oauth.token.url": "https://api.infusionsoft.com/token",
  "pagination.max": "100",
  "event.vendor.type": "webhook",
  "oauth.scope": "full",
  "oauth.user.token": "INFUSIONSOFT_USER_TOKEN",
  "oauth.authorization.url": "https://signin.infusionsoft.com/app/oauth/authorize",
  "event.notification.callback.url": null,
  "oauth.callback.url": "https://mycoolapp.com/auth",
  "oauth.user.refresh_token": "OAUTH_REFRESH_TOKEN",
  "oauth.user.refresh_interval": "28800",
  "oauth.api.key": "INFUSIONSOFT_API_KEY",
  "oauth.user.refresh_time": "1436369668710",
  "event.notification.enabled": "false"
},
"eventsEnabled": false,
"cachingEnabled": false,
"traceLoggingEnabled": false
}
```