

Weebly Events

Last Modified on 01/16/2019 3:25 pm EST

SAP Cloud Platform Open Connectors currently supports events via **polling** or **webhooks** depending on the endpoint.

- **Polling** is a mechanism where SAP Cloud Platform Open Connectors executes the configured query every `n` minutes and captures the changed information.
- **Webhooks** are when the provider lets SAP Cloud Platform Open Connectors know what information has changed. Note that additional endpoint setup may be required prior to creating your connector instance.

Note: SAP Cloud Platform Open Connectors normalizes only the `objectId`, `objectType`, and `eventType` event data. Event data also contains raw data, which the provider returns. The raw data varies based on the endpoint.

If you would like to see more information on our Events framework, please see [Events Overview](#).

SAP Cloud Platform Open Connectors supports webhook events for Weebly.

Webhooks

In order to enable webhooks, add this data to your `manifest.json`:

```

////////////////////////////////////
////////BASIC APP STRUCTURE////////
////////////////////////////////////
{
  "manifest": "1",
  "client_id": "INSERT_CLIENT_ID",
  "version": "2.0.0",
  "manage_app_url": "https://mycoolapp.com",
  "callback_url": "https://mycoolapp.com/auth",
  "oauth_final_destination": "editor",
  "locale": {
    "default": "en-us",
    "supported": ["en-us"]
  },
  //////////////////////////////////////
  ///WITH WEBHOOKS ENABLED////////
  //////////////////////////////////////
  "webhooks": {
    "callback_url": "https://console.cloud-elements.com/elements/api-v
2/weebly/events",
    "events": ["store.product.create", "store.product.update", "store.
product.delete",
    "store.cart.create", "store.cart.update"]
  }
}

```

This `manifest.json` must be uploaded when you create your app. For more information on creating your app, see [Weebly API Provider Setup](#).

Add the following two configurations to the `instance.json`:

```

"event.notification.enabled": "true",
"event.notification.callback.url": ""

```

instance JSON with polling events enabled:

```
{
  "element": {
    "key": "weebly"
  },
  "providerData": {
    "code": "Code on Return the URL"
  },
  "configuration": {
    "oauth.api.key": "",
    "oauth.api.secret": "",
    "site.id": "",
    "event.notification.enabled": "true",
    "event.notification.callback.url": ""
  },
  "tags": [
    ""
  ],
  "name": ""
}
```
