

Box - How To Post Custom Fields

Last Modified on 04/15/2019 1:28 pm EDT

There is a specific order in which custom fields can be posted through API calls to files in Box. The following is an example using sample payload data that can be used as a reference when verifying the necessary API calls to make.

1. `GET /folders/content` or utilize another API call to determine the file ID for an example file.

2. `GET /custom-fields/enterprise-templates`

or

```
POST /custom-  
fields/templates
```

```
{  
  "displayName": "Example Template",  
  "fields": [  
    {  
      "description": "Custom Field Example",  
      "displayName": "CustomField",  
      "hidden": false,  
      "key": "custom1",  
      "type": "string"  
    }  
  ],  
  "hidden": false,  
  "scope": "enterprise",  
  "templateKey": "customTemplate"  
}
```

Note the template key

3. `POST /files/{id}/custom-fields/{templateKey}/templates`

```
{  
  "scope": "enterprise"  
}
```

Note: This will associate the `customTemplate` template with the selected file.

4. `POST /files/{id}/custom-fields`

```
{  
  "path": "/custom1",  
  "scope": "enterprise",  
  "template": "customTemplate",  
  "value": "Custom Field Value"  
}
```

Note: this adds a custom field value to the template. The 'path' field in this POST must reference the fields.key from GET /custom-fields/enterprise-templates with a preceding forward slash.
