

Coupa Events

Last Modified on 03/16/2020 3:41 pm EDT

SAP Cloud Platform Open Connectors supports events via polling or webhooks depending on the API provider. For more information about our Events framework, see [Events Overview](#).

Supported Events and Resources

SAP Cloud Platform Open Connectors supports polling events for Coupa. After receiving an event, SAP Cloud Platform Open Connectors standardizes the payload and sends an event to the configured callback URL of your authenticated connector instance.

You can set up polling for the `accounts` resource. You can also copy the `accounts` configuration to poll other resources.

Note: Unless configured for a specific time zone, polling occurs in UTC.

Configure Polling Through the UI

To configure polling through the UI, follow the same steps to authenticate a connector instance, and then turn on events. Select the resources to poll, and then click **Create Instance**. For more information, see [Authenticate a Connector Instance with Events \(UI\)](#) or the connector-specific authentication topic.

Configure Polling Through API

Use the `/instances` endpoint to authenticate with Coupa and create a connector instance with polling enabled.

Note: The endpoint returns a connector token upon successful completion. Retain the token for all subsequent requests involving this connector instance.

To authenticate a connector instance with polling:

1. Construct a JSON body as shown below (see [Parameters](#)):

```
{
  "element": {
    "key": "coupa"
  }
}
```

```
    },
    "name": "INSTANCE_NAME",
    "configuration": {
      "event.poller.configuration": {
        "accounts": {
          "url": "/hubs/businessspendmanagement/accounts?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
          "idField": "id",
          "datesConfiguration": {
            "updatedAtField": "updated-at",
            "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "updatedAtTimezone": "PST",
            "createdAtField": "created-at",
            "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "createdAtTimezone": "PST"
          }
        },
        "users": {
          "url": "/hubs/businessspendmanagement/users?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
          "idField": "id",
          "datesConfiguration": {
            "updatedAtField": "updated-at",
            "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "updatedAtTimezone": "PST",
            "createdAtField": "created-at",
            "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "createdAtTimezone": "PST"
          }
        },
        "orders": {
          "url": "/hubs/businessspendmanagement/orders?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
          "idField": "id",
          "datesConfiguration": {
            "updatedAtField": "updated-at",
            "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "updatedAtTimezone": "PST",
            "createdAtField": "created-at",
            "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
            "createdAtTimezone": "PST"
          }
        },
        "invoices": {
          "url": "/hubs/businessspendmanagement/invoices?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
          "idField": "id",
          "datesConfiguration": {
            "updatedAtField": "updated-at",
            "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX"
```

```
        "updatedDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "updatedDateTimezone": "PST",
        "createdDateField": "created-at",
        "createdDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "createdDateTimezone": "PST"
    }
},
"inventoryTransactions": {
    "url": "/hubs/businessspendmanagement/inventory-transactions?
where=updated_at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
    "idField": "id",
    "datesConfiguration": {
        "updatedDateField": "updated-at",
        "updatedDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "updatedDateTimezone": "PST",
        "createdDateField": "created-at",
        "createdDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "createdDateTimezone": "PST"
    }
},
"purchaseOrders": {
    "url": "/hubs/businessspendmanagement/purchase-orders?where=u
pdated_at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
    "idField": "id",
    "datesConfiguration": {
        "updatedDateField": "updated-at",
        "updatedDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "updatedDateTimezone": "PST",
        "createdDateField": "created-at",
        "createdDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "createdDateTimezone": "PST"
    }
},
"products": {
    "url": "/hubs/businessspendmanagement/products?where=updated_
at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
    "idField": "id",
    "datesConfiguration": {
        "updatedDateField": "updated-at",
        "updatedDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "updatedDateTimezone": "PST",
        "createdDateField": "created-at",
        "createdDateFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
        "createdDateTimezone": "PST"
    }
},
"contracts": {
    "url": "/hubs/businessspendmanagement/contracts?where=updated
_at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
    "idField": "id",
```

```

    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "suppliers": {
    "url": "/hubs/businessspendmanagement/suppliers?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "forms": {
    "url": "/hubs/businessspendmanagement/forms?where=updated_at>='{date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  }
},
"event.poller.refresh_interval": "15",
"event.notification.enabled": true,
"event.vendor.type": "polling",
"filter.response.nulls": "true",
"api.key": "xxxxxxxxxxxx",
"siteAddress": "xxxxxxxxxxxxxxxx"
}
}

```

2. Call the following, including the JSON body you constructed in the previous step:

```
POST /instances
```

Note: Make sure that you include the User and Organization keys in the header. For more information, see [Authorization Headers, Organization Secret, and User Secret](#).

3. Locate the `token` and `id` in the response and save them for all future requests using the connector instance.

Example JSON with Polling

instance JSON with polling events enabled:

```
{
  "element": {
    "key": "coupa"
  },
  "name": "INSTANCE_NAME",
  "configuration": {
    "event.poller.configuration": {
      "accounts": {
        "url": "/hubs/businessspendmanagement/accounts?where=updated_at>=${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
        "idField": "id",
        "datesConfiguration": {
          "updatedAtField": "updated-at",
          "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
          "updatedAtTimezone": "PST",
          "createdAtField": "created-at",
          "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
          "createdAtTimezone": "PST"
        }
      },
      "users": {
        "url": "/hubs/businessspendmanagement/users?where=updated_at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
        "idField": "id",
        "datesConfiguration": {
          "updatedAtField": "updated-at",
          "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
          "updatedAtTimezone": "PST",
          "createdAtField": "created-at",
          "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
          "createdAtTimezone": "PST"
        }
      },
      "orders": {
        "url": "/hubs/businessspendmanagement/orders?where=updated_at>='${date:yyyy-MM-dd'T'HH:mm:ssXXX}'",
```

```
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "invoices": {
    "url": "/hubs/businessspendmanagement/invoices?where=updated_at>='
    ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "inventoryTransactions": {
    "url": "/hubs/businessspendmanagement/inventory-transactions?where
    =updated_at>=' ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "purchaseOrders": {
    "url": "/hubs/businessspendmanagement/purchase-orders?where=update
    d_at>=' ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "products": {
```

```
    "url": "/hubs/businessspendmanagement/products?where=updated_at>='
    ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "contracts": {
    "url": "/hubs/businessspendmanagement/contracts?where=updated_at>='
    ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "suppliers": {
    "url": "/hubs/businessspendmanagement/suppliers?where=updated_at>='
    ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "id",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  },
  "forms": {
    "url": "/hubs/businessspendmanagement/forms?where=updated_at>='
    ${date:yyyy-MM-dd'T'HH:mm:ssXXX}' ",
    "idField": "",
    "datesConfiguration": {
      "updatedAtField": "updated-at",
      "updatedAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "updatedAtTimezone": "PST",
      "createdAtField": "created-at",
      "createdAtFormat": "yyyy-MM-dd'T'HH:mm:ssXXX",
      "createdAtTimezone": "PST"
    }
  }
}
```

```

    }
  },
  "event.poller.refresh_interval": "15",
  "event.notification.enabled": true,
  "event.vendor.type": "polling",
  "filter.response.nulls": "true",
  "api.key": "xxxxxxxxxxxx",
  "siteAddress": "xxxxxxxxxxxxxxxx"
}
}

```

Parameters

API parameters not shown in SAP Cloud Platform Open Connectors are in

`code formatting` .

Parameter	Description	Data Type
<code>key</code>	The connector key. coupa	string
Name <code>name</code>	The name for the connector instance created during authentication.	Body
<code>api.key</code>	The Coupa api key.	string
<code>siteAddress</code>	The Coupa site address	string
Events Enabled <code>event.notification.enabled</code>	<i>Optional.</i> Identifies that events are enabled for the connector instance. Default: <code>false</code> .	boolean
Event Notification Callback URL <code>event.notification.callback.url</code>	The URL where you want SAP Cloud Platform Open Connectors to send the events.	string
Event poller refresh interval (mins) <code>event.poller.refresh_interval</code>	A number in minutes to identify how often the poller should check for changes.	number
Configure Polling <code>event.poller.configuration</code>	Optional*. Configuration parameters for polling.	JSON object
URL <code>url</code>	The url to query for updates to the resource.	String

ID Field Parameter	Description	Data Type
Advanced Filtering <code>datesConfiguration</code>	Configuration parameters for dates in polling	JSON Object
Updated Date Field <code>updatedDateField</code>	The field that identifies an updated object.	String
Updated Date Format <code>updatedDateFormat</code>	The date format of the field that identifies an updated object.	String
Created Date Field <code>createdDateField</code>	The field that identifies a created object.	String
Created Date Format <code>createdDateFormat</code>	The date format of the field that identifies a created object.	String
tags	<i>Optional.</i> User-defined tags to further identify the instance.	string